



INJECTA

the perfect dosing



CLEANING SYSTEMS DIVISION

- DISHWASHER PRODUCTS
- WASHING MACHINE PRODUCTS
- DILUTION & DISINFECTION PRODUCTS
- SOAP & PAPER DISPENSER PRODUCTS
- ANTI-COVID PRODUCTS



CATALOGUE

2022


www.injecta.com





WASHING MACHINE PRODUCTS





NIKE SERIES

POMPE PERISTALTICHE - PERISTALTIC PUMPS

CARATTERISTICHE GENERALI / GENERAL FEATURES



- Adatte per liquidi viscosi
 - Lunga durata del tubo
 - Fissaggio a parete tramite staffa ad aggancio rapido
 - Contenitore ip65 ignifugo e antiacido
 - Interruttore on/off completamente protetto
 - Possibilità di personalizzazione su richiesta
-
- Suitable for viscous liquids
 - Long life tube
 - Quick wall mounting
 - Fireproof and antiacid IP65 case
 - On/off switch completely protected
 - Possibility of customization on the pump head (upon request)

NK FX 250

PORTATE FLOW RATES	PRESSIONI PRESSURES	ALIMENTAZIONE POWER SUPPLY	DISLOCAMENTO PER GIRO DISPLACEMENT PER REVOLUTION	RACCORDI FITTINGS
Variabile - Variable 15 lt/h	100 kPa (1bar-14,5 psi)	100÷240 Vac, 24 Vac / 20÷265 Vac Comando tramite segnale esterno Activated through an external signal	3 ml	Portagomma - Rubber Ø8x12 mm



0%5584ENK

- Tubo peristaltico EPDM
- EPDM peristaltic tube



0%5584NK

- Tubo peristaltico silicone
- Silicon peristaltic tube




0%5569NKTL

- Tubo peristaltico Santoprene
- Santoprene peristaltic tube




0%5582

- Tubo PVC morbido Ø 8x12 (50 mt)
- PVC soft tube Ø 8x12 (50 mt)



11201

- Supporto di fissaggio a parete
- Wall mounting bracket



NIKE SERIES

POMPE PERISTALTICHE - PERISTALTIC PUMPS

CARATTERISTICHE GENERALI / GENERAL FEATURES



- Pompa programmabile per detergente
 - Timer integrato a microprocessore
 - Dosaggio temporizzato 0÷999 sec. Con abilitazione da segnale
 - Menu di programmazione parametri protetto da password (0÷999)
 - Controllo del blocco motore e dello spunto iniziale con visualizzazione allarme in caso di sovraccarico sul motore e gestione dei tentativi di partenza
 - Tubi epdm/silicone
-
- Programmable pump for detergent
 - Microprocessor integrated timer
 - Signal-triggered timed dosing 0÷999 sec.
 - Parameters setting menu protected by password (0÷999)
 - Control of the motor and of the initial start up through an alarm visualization in case of overload on the motor and management of starting attempts
 - EPDM/silicon tube

NK TL 250

PORTATE FLOW RATES	PRESSIONI PRESSURES	ALIMENTAZIONE POWER SUPPLY	DISLOCAMENTO PER GIRO DISPLACEMENT PER REVOLUTION	RACCORDI FITTINGS
Fissa - Fixed 15 lt/h	100 kPa (1bar-14,5 psi)	100÷240 Vac, 24 Vac / 20÷265 Vac Comando tramite segnale esterno Activated through an external signal	3 ml	Portagomma - Rubber Ø8x12 mm



0%5584ENK

- Tubo peristaltico EPDM
- EPDM peristaltic tube



0%5584NK

- Tubo peristaltico silicone
- Silicon peristaltic tube




0%5569NKTL

- Tubo peristaltico Santoprene
- Santoprene peristaltic tube



0%5582

- Tubo PVC morbido Ø 8x12 (50 mt)
- PVC soft tube Ø 8x12 (50 mt)



11201

- Supporto di fissaggio a parete
- Wall mounting bracket