



fluimac
pump solution

AODD PUMPS

www.fluimac.com

ENGLISH 

P 700



PP



PVDF+CF



ALU



SS


TECHNICAL DATA

Fluid connections	2" BSPP-DN 50
Air connection	3/4" BSPP
Max. Flow rate	700 lt/min
Max air pressure	8 bar
Max delivery head	80 m
Max Suction Lift Dry	5 m
Max Suction Lift Wet	9,8 m
Max Solid passing	8,5 mm
Noise level:	78 dB
Max Viscosity:	50.000 cps
Displacement per Stroke:	3050 CC ~

II 3/3 G Ex h IIB T4 Gc
II 3 D Ex h IIB T135°C Dc X

Displacement per stroke may vary based on suction condition, discharge head, air pressure and fluid type.


PERFORMANCE



The curves and performance values refer to pumps with submerged suction and a free delivery outlet with water at 20°C. These data may vary according to the construction materials and hydraulic conditions.

DIMENSIONS

	A	B	C	Net Weight	Temperature
PP	595 mm	345 mm	570 mm	30,6 kg	- 4 °C + 65 °C
PVDF	595 mm	345 mm	570 mm	41,6 kg	- 20 °C + 95 °C
ALU	595 mm	340 mm	567 mm	37,6 kg	- 20 °C + 95 °C
SS	487 mm	340 mm	599 mm	51 kg	- 20 °C + 95 °C



COMPOSITION

MODEL	CASING	DIAPHRAGM	BALLS	SEATS	GASKET	CONNECTIONS	ATEX	PORTS
P0700	P = PP KC = PVDF+CF S = SS A = ALU	HT = HYTREL+PTFE MT = SANTOPRENE+PTFE H = HYTREL W = SANTOPRENE H.R. D = EPDM N = NBR	T = PTFE S = SS D = EPDM N = NBR	P = PP K = PVDF S = SS Z = PE-UHMWE	D = EPDM V = VITON N = NBR T = PTFE	1 = BSP 2 = FLANGED 5 = NPT	- = zone 2	AB = STANDARD EF = STANDARD SS